## Metal Rules Grade 1 of JIS B7516-2005(abstract)

as of October, 2018

## Conversion table

)							
Grade 1 of JIS B7516-2005							
SUS420 J2 of JIS G 4305 or that equivalent or superior to this in quality.							
H√400 min							
Nominal Size	Overall Length(L)		Thickness(T)		Width(W)		
	Size	Tolerance	Size	Tolerance	Size	Tolerance	
150	175		0.5	- ±10%	15	±2%	
300	335		1.0		25		
600	640	±Emm	1.2		30		
1,000	1,050	TOIIIII	1.5		35		
1,500	1,565		2.0		40		
2,000	2,065		2.0		40		
The							
Nominal Size	Straigh	htness	Nominal Size		Straightness		
150	0.23 max		1,000		0.40 max		
300	0.26 max		1,500		0.50 max		
600	0.32 max		2,000		0.60 max		
The squareness of the scale end face of a rule in respect of its scale side shall be 0.035mm max per 10mm length of the end face.							
Length		Tolerance					
Ler	ngth			10161	arice		
Ler	ngth 500	max			.15		
Ler over 500 ~	500			±0			
	500 ~ 1,000	max		±0	.15		
	SUS420 J2 of JI  Nominal Size  150  300  600  1,000  2,000  The  Nominal Size  150  300  600  The squ respect	SUS420 J2 of JIS 6 4308     SUS420 J2 of JIS 6 4308     Nominal Size	Sus420 J2 of JIS G 4305 or that e	SUS420 J2 of JIS G 4305 or that equivalent	SUS420 J2 of JIS G 4305 or that equivalent or superior	SUS420 J2 of JIS 6 4305 or that equivalent or superior to this in Hv400 min	

Items	Inch Conversion Chart (TAP DRILL WW.UNC)	Measurement Conversion Chart					
		Length	Width	Weight	Volume		
Hard Chrome Finish 15cm	•						
30cm	•						
60cm	•						
1m	•						
Metric x Shaku 15cm left		•	•				
30cm left		•	•				
60cm left		•	•	•			
1 m left		•	•	•	•		
1 m right	•						
Polish Finish 15cm	•						
30cm	•						
60cm	•						
1m	•						
Pickup 10cm		•					
15cm		•	•				
30cm		•	•				
60cm		•	•	•			
1m		•	•	•	•		
With Scale Stopper 15cm	•						
30cm	•						
1mm Dividing 15cm	•						
30cm	•						
60cm	•						
1m	•						
Mini 15cm	•						

■Material Less than 2m: Stainless steel SUS420J2 Over 3m: Stainless steel SUS304

(SUS means STELL STAINELSS-rust-resistant. Hv means HARD VICKERS -unit for hardness.)

All of our stainless rules are registered as Japanese Industrial Standard (JIS) under the specifications above. Although some of rules exceed JIS specifications due to unusual graduations, shapes, or sizes, all of our products, regardless of registration, have gone through strict product inspections based on the JIS specifications above to provide safe, high quality products. SUS420J2 has baking finish. SUS304 doesn't have baking finish. Length tolerance over 3m: 3m±0.5mm, 4m±0.65mm, 5m±0.8mm, 6m±0.95mm